



ELLIPSOIDAL P6-CTO

BI COLOR LED PROFILE LIGHT

SPECIAL FEATURES

Light body: Aluminum body
Color Temperature: 3000K-6500K
Color Rendering Index(CRI):
Ra≥90 Silent Operation
Flicker Free Operation



ALS LED PROFILE SERIES P400 IS NEWLY DEVELOPED LED FIXTURE WITH BI-COLOR 3200K-6500K , THE FLICKER-FREE OPERATION & SUPERB COOLING TECHNOLOGY- MAKE THIS SERIES UNIQUE. - SUITABLE FOR STUDIO,FUNCTION HALL & TOURING.

Light Source

LED POWER: 600W
LED Color: 2in1 CW+WW
Color temperature : 3000K-6000K
LED Life Time: Over 50,000 hours

Power Supply

Voltage: AC100-240V
Max.power: 350W

Optic / Photometrics

Beam Angle: 10° , 19°(Standard) , 26° , 36° , 50°
Color Rendering Index(CRI): Ra≥90
Illuminance: 19°- 4850 lux @ 5M
Light Projection distance: 3-12 Meters

Dimmer Effect

Dimming Curve: 4 kinds
Dimming
Frequency: 500HZ – 25000HZ optional
Strobe : 1–25times/sec



ELLIPSOIDAL P6-CTO

BI COLOR LED PROFILE LIGHT

Control

Control Protocol: RDM / DMX
Control System: DMX, Auto run and Master/Slave
DMX Channels: 5CH(2in1)

Working Enviroment

Working Temperature: -10°C ~40°C
Cooling system: Low noise fan cooling
IP Grade: IP20 (indoor)

Packing

Net Weight : 9.5kgs
Gross Weight: 11.5kgs
Packing Size: 75*32.5*35cm(1pc/carton)
Warranty Time: 1 Year warranty

Photographic Chart

