



FRESNEL F6-CTO IP

OUTDOOR BI COLOR LED FRESNEL LIGHT

SPECIAL FEATURES

Light body:	Die casting aluminum
Touch screen:	LCD with touch screen
Ingress Protection:	IP54
Color Temperature::	3000K-6000K
Color Rendering Index(CRI):	Ra≥90
Flicker Free operation	



Light Source

LED POWER:	600W
LED Color:	2in1 CW+WW
Color temperature :	3000K-6000K
LED Life Time:	Over 50,000 hours

Power Supply

Voltage:	AC100-240V
Max.power:	300W

Optic / Photometrics

Beam Angle:	15°- 50°
Zoom Function:	Auto zoom by DMX
Color Rendering Index(CRI):	Ra≥90
Illuminance:	50°-1800 lux @ 5M 15°-8300 lux @ 5M

Dimmer Effect

Dimming Curve:	4 kinds
Dimming	
Frequency:	500HZ – 25000HZ optional
Strobe :	1-25times/sec

*The **ALS FRESNEL F6-CTO IP** is an outdoor LED Fresnel, build with high temperature strengthen cast aluminum casing with modern outlook. Equipped with 300W 3000K + 300W 6000K COB Lamp. The fixture is designed and manufactured strictly following CE&RoHS standards, complying with international standard DMX512 protocol. It's available independently controlled and linkable with each other for operation. And it is applicable for large-scale outdoor live performances, theater, studio, nightclubs, entertainment venues and Outdoor Theme Park.*



F6-CTO IP

OUTDOOR BI COLOR LED FRESNEL LIGHT

Control

Control Protocol: RDM / DMX
Control System: DMX, Auto run and Master/Slave
DMX Channels: 5CH(2in1)

Working Enviroment

Working Temperature: -10°C ~40°C
Cooling system: Fan-less no noise
IP Grade: IP54 waterproof

Packing

Net Weight : 13kgs
Gross Weight: 16kgs
Packing Size: 67*38.5*39cm(1pc/carton)
Warranty Time: 1 Year warranty

Photographic Chart (Spectrogram & CRI) Ra≥90

