



FRESNEL F6-CTO

BI COLOR LED FRESNEL LIGHT

SPECIAL FEATURES

Light body:	Aluminum body
Easy Access:	LCD with Direct knob control
Color Temperature:	3000K-6500K
Color Rendering Index(CRI):	Ra≥90
Silent Operation	
Flicker Free Operation	



Light Source

LED POWER:	600W
LED Color:	2in1 CW+WW
Color temperature :	3000K-6000K
LED Life Time:	Over 50,000 hours

Power Supply

Voltage:	AC100-240V
Max.power:	350W

Optic / Photometrics

Beam Angle:	15° - 50°
Zoom Function:	Auto zoom by DMX
Color Rendering Index(CRI):	Ra≥90
Illuminance:	50°-1800 lux @ 5M 15°-7500 lux @ 5M
Light Projection distance:	3-10 Meters

Dimmer Effect

Dimming Curve:	4 kinds
Dimming	
Frequency:	500HZ - 25000HZ optional
Strobe :	1-25times/sec

*The **ALS FRESNEL F6-CTO** is new design with high temperature strengthen cast aluminum casing with modern outlook. Equipped with 300W 3000K + 300W 6500K COB Lamp. The fixture is designed and manufactured strictly following CE&RoHS standards, complying with international standard DMX512 protocol. It's available independently controlled and linkable with each other for operation. And it is applicable for large-scale live performances, theater, studio, nightclubs and entertainment venues.*



FRESNEL F6-CTO

BI COLOR LED FRESNEL LIGHT

Control

Control Protocol: RDM / DMX
Control System: DMX, Auto run and Master/Slave
DMX Channels: 5CH(2in1)

Working Enviroment

Working Temperature: -10°C ~40°C
Cooling system: Low noise fan cooling
IP Grade: IP20 (indoor)

Packing

Net Weight : 8.5kgs
Gross Weight: 10.5kgs
Packing Size: 67*38.5*39cm(1pc/carton)
Warranty Time: 1 Year warranty

Photographic Chart (Spectrogram & CRI) Ra≥90

