

FS1000mk2 Followspot Light

ALS FS1000mk2 Followspot light, Equipped with 1000W High brightness LED Module with improved brightness compare to the earlier version, Sideways mounted handles are designed to allow access to the control buttons on the rotate-able rear-mounted display panel. Control of parameters may be set via the control buttons or remotely from your console, leaving the operator to concentrate on actual follow spotting. Superb and low noise cooling system is specifically designed to operate in any noise-sensitive environment, TV use enhanced with flicker-free operation.

FS1000mk2 is supplied with a handle, manual iris, robust tripod, mounting adapter and flightcase.



1000W mk2 8°%/RMIDE (hux) 0 30000 14000 8300 5560 3910 2172 1390 965 709 543 429 347.5 6%/RMIDE (hux) 0 41800 20000 12270 8200 5736 3203 2050 1423 1050 800 632 512 ALS

TECHNICAL SPECIFICATIONS

POWER

Voltage:AC100V-AC240V 50Hz

Rated Power: 1300W

LIGHT SOURCE

Lamp Type: High power 1000W module Color Rendering Index (CRI): Ra>90,

OPTIC

Dimmer;0-100% linearly adjustable

Beam Angle:5-10 degree linear magnification focusing function

Average LED Lifetime:over 50,000 hours

Color temperature: Adjustable 3200K 5600K 8500K

Iris Control: Yes

COLOR

Red orange yellow green blue + white light

CONTROL

Control Mode: Manual -DMX is available for internal function Rotate-able control surface for ease of better operation

PHOTOMETRICS

Illuminance @ 10M: 41800 lux Illuminance @ 30M: 5736 lux Illuminance @ 50M: 2050 lux

Light projection distance : 10-100 meters Color Temperature : 3200K-8500K

BODY FEATURES

Light body:Light body mady, small size, Light weight, high brightness

Color:Black

Stand: Heavy duty solid stand

Power connection:Powercon Data;3pin

XLR in & Out

WORKING ENVIROMENT

-15 °C to 40 °C

Cooling System:12 pcs of 8mm thick copper tubes are used to conduct heat through the large surface Product of aluminum heat dissipation, to ensure that the

LED lamp beads to achieve the best cooling

Effect

System IP Grade: IP20

DIMENSION & WEIGHT

FS1000W Packaging:

Body size: 1205 * 375.5 * 422.7 mm

Net body weight: 38 KG

Bracket & stand size: 1200 * 240 * 200 MM

Weight of bracket: 7.8 KG

Flightcase size: 1310 * 600 * 620MM

Flightcase weight: 36.5

Total weight of flightcase packing: 80KG







